

Models 220600 / 220650

Braeburn 220600 and 220650 Humidifiers offer an economical solution to whole house humidification! Delivering up to 17 gallons per day, these models provide humidification for up to 3,904 square feet. Choose the 220600 with a manual humidistat, or upgrade your customer with the 220650 and get our advanced humidistat that automatically adjusts based on outdoor temperature. Installation is quick and easy, and will provide years of reliable operation.

Bypass Flow-Through Humidifiers



220600



Includes
Manual Humidistat
Model 229100

220650



Includes
Digital Humidistat
Model 229150

Easy Installation!
Simple Operation!
Promotes Increased Comfort!
Automatic Humidity Control!*

Product Features

- Preassembled for Quick Installation
- Patented KineticFlo® Water Distribution Tray Assures High Performance
- Delivers up to 17 Gallons Per Day
- Up to 3,904 Sq. Ft. Coverage
- UV Resistant DuraPlast® Pad Frame
- Integrated Bypass Damper with Reversible Cover
- Includes Transformer and Saddle Valve Kit
- Stainless Steel Solenoid Valve Seat

The
brighter
choice®



* Model 220650

For more information, contact your local distributor, visit our web site at www.braeburnonline.com, or call our sales department at 1-866-268-5599.

No. 2206-300-02 ©2013 Braeburn Systems LLC • 2215 Cornell Avenue, Montgomery, Illinois 60538 • 630-844-1968 • All Rights Reserved • Made in U.S.A.

Models 220600 / 220650

Bypass Flow-Through Humidifiers

Architectural Specifications

The humidifier shall be a Braeburn® item number 220600 or 220650 bypass flow through type measuring 16-1/2" high x 12" wide x 10" deep. The bypass duct shall have a 6" diameter and the plenum opening shall be 12" high x 8-3/4" wide. The Braeburn humidifier shall be powered by 24 Volts AC, installed on the supply side of a forced air furnace and controlled by a 24 Volt AC manual or digital humidistat. The 220600 shall include a Braeburn 229100 manual humidistat. The 220650 shall include a Braeburn 229150 digital automatic humidistat. The humidifier shall allow the evaporation of up to 17 gallons of water per day and provide humidification in homes up to 3,904 square feet. The replaceable humidifier pad shall be item number 229019, and should be replaced at least once per year. The humidifier shall include a 24 Volt AC transformer and a self piercing saddle valve kit for attaching to a water supply of either copper, steel, brass or hard plastic pipe.

Specifications

Power	24 VAC
Gallons Per Day	Up to 17
Size	16 1/2"H x 12"W x 10"D
Plenum Opening	12"H x 8 3/4"W
Bypass Duct	6" Diameter
Replacement Pad	229019

Shipping Information

Quantity	1
Dimensions	13 1/2"H x 18 1/4"W x 9 3/4"D
Weight	7.15 lbs.
Cubic Feet	1.39
Pallet Qty.	30

Available Parts & Accessories

229100	Manual Humidistat - Duct Mount
229110	Manual Humidistat Wall Mount Kit
229150	Digital Humidistat - Duct or Wall Mount
229019	Humidifier Pad
229004	Strainer Screen
229019	Humidifier Pad
229040	Solenoid Valve (24 VAC)
229050	Current Sensing Relay (24 VAC)
229051	Current Sensing Relay (120 VAC)

The Braeburn 220600 / 220650 Replaces:*

Honeywell®	260A, 260B, 265A, 265B
Aprilaire®	600A, 600M, 560
Skuttle®	2001, 2101
GeneralAire®	900, 900XM, SL16, 1042
Trion®	G300

* Verify specific application requirements.

All trademarks are the property of their respective owners.

Braeburn Humidifier Selection Guide

Based on House Size (sq. ft.) and Type of Construction

Braeburn Model	Gallons Per Day	Loose	Average	Tight
220500 / 220550	12	1,303	1,846	2,856
220600 / 220650	17	1,782	2,523	3,904
220700 / 220750	18	1,924	2,723	4,214

NOTE: Figures are based on an 8 ft. ceiling height. GPD shown is a 120° plenum temperature. Square footage may be adjusted for other plenum temperatures. Humidity based on 70°F / 35% Relative Humidity Indoor Condition Using ARI Guideline F Humidity Load Determination Method.

For more information, contact your local distributor, visit our web site at www.braeburnonline.com, or call our sales department at 1-866-268-5599.